Safety Data Sheet



SECTION 1 - IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Chemical Nature: Alkyl silanes/siloxane solution.

Trade Name: VenSeal Ultra WB

Product Use: Water based water and oil repellent penetrating sealer for concrete, stone and masonry.

Product Code: PSUWB

Creation Date: September, 2017

This version issued: November, 2020 and is valid for 5 years from this date.

Poisons Information Centre: Phone 13 1126 from anywhere in Australia

SUPPLIER CONTACT INFORMATION:

Name: Illawarra Coatings Pty. Ltd.

Address: 19 Technology Drive, APPIN NSW 2560. PO Box 95, APPIN NSW 2560

Telephone: 61.2.4631 2200 **Facsimile**: 61.2.4631 2233

Website: https://illawarracoatings.com/ **Email**: info@illawarracoatings.com

Emergency: 0414 874 494 (24 hours, 7 days a week)

SECTION 2 - HAZARDS IDENTIFICATION

Statement of Hazardous Nature

This product is classified as hazardous according to the criteria of NOHSC. Not subject to the ADG Code when transported in Australia by Road or Rail.

SUSMP Classification: None allocated.

ADG Classification: N/A UN Number: N/A



GHS Signal word: WARNING

Eye Damage /Irritation: Category 2A Skin Corrosion/Irritation: Category 2

HAZARD STATEMENT:

H315: Causes skin irritation.

H319: Causes serious eye irritation.

RESPONSE

P264: Wash skin thoroughly after handling.

P280: Wear protective gloves, protective clothing and eye or face protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do so. Continue rinsing.

P332+P313: If skin irritation occurs, get medical advice/attention. P337+P313: If eye irritation persists, get medical advice/attention.

P362: Take off contaminated clothing and wash before reuse.

STORAGE

P410: Protect from sunlight.

P411: Store at temperatures not exceeding 30°C.

P402+P404: Store in a dry place. Store in a closed container.

DISPOSAL

P501: If they cannot be recycled, dispose of contents to an approved waste disposal plant and containers to landfill (see Section 13 of this SDS).

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS STEL (mg/m³) **Ingredients CAS No** Conc,% TWA (mg/m³) Alkyl silane/siloxane solution 6-10% N/A not set not set Water to 100

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non-hazardous ingredients are also possible.

The SWA TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that may be equalled (but should not be exceeded) for no longer than 15 minutes and should not be repeated more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak "is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

SECTION 4 - FIRST AID MEASURES

General Information: You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 1126 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this SDS with you when you call.

Inhalation: Remove victim to fresh air and obtain medical attention if health effects occur or persist.

Skin Contact: Quickly and gently blot away excess liquid. Wash gently and thoroughly with warm water (use non-abrasive soap if necessary) for 10-20 minutes or until product is removed. Under running water, remove contaminated clothing, shoes and leather goods (e.g. watchbands and belts) and completely decontaminate them before reuse or discard. If irritation persists, repeat flushing and seek medical attention.

Eye Contact: Quickly and gently blot material from eyes. Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 15 minutes or until the product is removed, while holding the eyelid(s) open. Take care not to rinse contaminated water into the unaffected eye or onto the face. Obtain medical attention immediately. Take special care if exposed person is wearing contact lenses. Urgently get medical attention.

Ingestion: If swallowed, do NOT induce vomiting. Wash mouth with water and contact a Poisons Information Centre or call a doctor.

SECTION 5 - FIRE FIGHTING MEASURES

Fire and Explosion Hazards: The major hazard in fires is usually inhalation of heated and toxic or oxygen deficient (or both), fire gases. There is little risk of an explosion from this product if commercial quantities are involved in a fire.

Fire decomposition products from this product may be toxic if inhaled. Take appropriate protective measures.

Extinguishing Media: In case of fire, use carbon dioxide, dry chemical, foam, dry sand. Alcohol resistant foam is the preferred firefighting medium but, if it is not available, normal foam can be used. Try to contain spills, minimise spillage entering drains or water courses.

Fire Fighting: Flammable hydrogen gas may be produced on prolonged contact with metals such as aluminium, tin, lead and zinc. Aqueous solution, not flammable under normal conditions of use. Flammable hydrogen gas may be produced on prolonged contact with metals such as aluminium, tin, lead and zinc.

Flash point: No data. **Upper Flammability Limit:** No data. **Lower Flammability Limit:** No data. **Autoignition temperature:** No data. Flammability Class: No data.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Accidental release: Spilled material is very slippery. Only water will evaporate from a spill of this material. Dries to form glass film which can easily cut skin. Sinks and mixes with water. High pH of this material is harmful to aquatic life.

Clean up methods: For small spills, mop up and neutralise liquid, then discharge to sewer in accordance with federal, state and local regulations or permits. For large spills, keep unnecessary people away; isolate hazard area and deny entry. Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent runoff from entering into storm sewers and ditches which lead to natural waterways. Isolate, dike and store discharged material, is possible. Use sand or earth to contain spilled material. If containment is impossible, neutralise contaminated area and flush with large quantities of water.

SECTION 7 - HANDLING AND STORAGE

Precautions for safe handling: Avoid contact with eyes, skin and clothing. Avoid breathing spray mist. Keep containers closed. Promptly clean residue from closures with cloth.

Conditions for safe storage: Keep containers closed at all times. Store away from acids and foodstuffs. Store in clean steel or plastic containers. Separate from acids, reactive metals and ammonium salts. Storage temperature 0 - 95°C. Loading temperature 45 - 95°C. Do not store in aluminium, fibreglass, copper, brass, zinc or galvanised containers. Mild steel is the most suitable material of construction for drums, tanks, valves, pipework, etc. Concrete storage tanks can be used but must be strong enough to hold the weight of Potassium Silicate solution to be stored and thick enough to prevent seepage of water.

SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION

Exposure control, personal protection: The following Australian Standards will provide general advice regarding safety clothing and equipment: Respiratory equipment: AS/NZS 1715, Protective Gloves: AS 2161, Occupational Protective Clothing: AS/NZS 4501 set 2008, Industrial Eye Protection: AS1336 and AS/NZS 1337, Occupational Protective Footwear: AS/NZS2210.

Exposure limits have not been established by SWA for any of the significant ingredients in this product.

No special equipment is usually needed when occasionally handling small quantities. The following instructions are for bulk handling or where regular exposure in an occupational setting occurs without proper containment systems.

Ventilation: This product should only be used in a well ventilated area. If natural ventilation is inadequate, use of a fan is suggested.

Eye Protection: Protective glasses or goggles should be worn when this product is being used. Failure to protect your eyes may cause them harm. Emergency eye wash facilities are also recommended in an area close to where this product is being used. **Skin Protection:** If you believe you may have a sensitisation to this product or any of its declared ingredients, you should prevent skin contact by wearing impervious gloves, clothes and, preferably, apron. Make sure that all skin areas are covered. See below for suitable material types.

Protective Material Types: We suggest that protective clothing be made from the following materials: neoprene, butyl rubber. **Respirator:** Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned above. Otherwise, not normally necessary.

Eyebaths or eyewash stations and safety deluge showers should, if practical, be provided near to where this product is being handled commercially.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES:

Physical Description & colour:White homogeneous liquid.Odour:Characteristic odour.Boiling Point:>100°C at 100kPa.

Freezing/Melting Point: No specific data. Liquid at normal temperatures.

Volatiles:
No data.
Vapour Pressure:
No data.
Vapour Density:
No data.
Specific Gravity:
1.00 +/- 0.01 kg/l

Water Solubility: Soluble.

pH: 7-8.

Volatility: No data.

Odour Threshold: No data.

Evaporation Rate: No data.

Coeff Oil/water Distribution: No data.

Viscosity: 100-500 cps (temperature not stated)

Autoignition temp: No data.

SECTION 10 - STABILITY AND REACTIVITY

Reactivity: This product is unlikely to react or decompose under normal storage conditions. However, if you have any doubts, contact the supplier for advice on shelf life properties.

Conditions to Avoid: This product should be kept in a cool place, preferably below 30°C. Keep containers tightly closed.

Containers should be kept dry. Keep containers and surrounding areas well ventilated.

Incompatibilities: strong acids, oxidising agents.

Fire Decomposition: Combustion forms carbon dioxide, and if incomplete, carbon monoxide and possibly smoke. Water is also formed. May form hydrogen chloride gas, other compounds of chlorine. Carbon monoxide poisoning produces headache, weakness, nausea, dizziness, confusion, dimness of vision, disturbance of judgment, and unconsciousness followed by coma and death

Polymerisation: Polymerisation reactions are unlikely; they are not expected to occur.

SECTION 11 - TOXICOLOGICAL INFORMATION

Acute toxicity - Oral: LD50, rat: Not determined. The acute oral toxicity of this product has not been tested.

Acute toxicity – Dermal: No data available.
Acute toxicity – Inhalation: No data available.
Acute toxicity – Respiratory: No data available.

Skin sensitization: No data available.

Germ cell mutagenicity: The mutagenic potential of this material has not been tested.

Carcinogenicity: There are no known reports of carcinogenicity of this product.

Reproductive toxicity STOT-single: No data available.

Aspiration hazard: No data available.

EYES: Possible chemical related eye burns resulting in a cloudy appearance of the cornea, pain, impairment or loss of vision. **SKIN:** Allergic skin effects such as redness, swelling, blistering and itching. Dermal effects may result in a change in skin pigmentation and/or colouration. Some individuals may experience sever skin reactions resulting in redness, swelling, itching, dryness, cracking, blistering and pain.

INHALATION: Upper respiratory tract irritation may result in cough, sneezing, nasal discharge, headache, hoarseness and nose and throat pain.

INGESTION: Irritation of the gastrointestinal tract may result in pain, abdominal tenderness, nausea, diarrhoea and vomiting.

REPRODUCTIVE: Not established for this product.

OTHER: Not established for this product.

SECTION 12 - ECOLOGICAL INFORMATION

General: Avoid contaminating waterways.

Ecotoxicity: No information available for this specific material.

Persistance and degradation: Silicone ingredients are not readily biodegradable. Hydrolysis products such as silanol and siloxanol can for polysiloxane. Elimination of polymers is by adsorption to activated sludge.

Mobility: Silicone content can be absorbed by floating particles and separation by sedimentation.

Bioaccumulative potential: Bioaccumulation is not expected to occur according to current knowledge.

SECTION 13 - DISPOSAL CONSIDERATIONS

Disposal: This product may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. If neither of these options is suitable in-house, consider controlled incineration, or contact a specialist waste disposal company.

SECTION 14 - TRANSPORT INFORMATION

Transport information: Not classified as a Dangerous Good according to the Australian Code for the Transport Dangerous GoodsbyRoadandRail. Not regulated for transport Dangerous Goods: ADG7, UN, IATA, IMDG.

SECTION 15 - REGULATORY INFORMATION

Poisons schedule: \$5

AICS: All of the significant ingredients in this formulation are compliant with NICNAS regulations.

SECTION 16 - OTHER INFORMATION

This SDS contains only safety-related information. For other data see product literature.

Acronyms:

ADG Code Australian Code for the Transport of Dangerous Goods by Road and Rail (7th edition)

Australian Inventory of Chemical Substances

SWA Safe Work Australia, formerly ASCC and NOHSC

CAS number Chemical Abstracts Service Registry Number

Hazchem Code Emergency action code of numbers and letters that provide information to emergency services

especially firefighters

IARC International Agency for Research on Cancer

NOS Not otherwise specified

NTP National Toxicology Program (USA)

R-Phrase Risk Phrase

SUSMP Standard for the Uniform Scheduling of Medicines & Poisons

UN Number United Nations Number

THIS SDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER MUST REVIEW THIS SDS IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE.

IF CLARIFICATION OR FURTHER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THE USER SHOULD CONTACT THIS COMPANY SO WE CAN ATTEMPT TO OBTAIN ADDITIONAL INFORMATION FROM OUR SUPPLIERS

OUR RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.

Please read all labels carefully before using product.

This SDS is prepared in accord with the SWA document "Preparation of Safety Data Sheets for Hazardous Chemicals - Code of Practice" (December 2011)